

Summary of corrections to Volume VI of the U.S. Coast Guard Light List for the 2003 edition.

(1) No.	(2) Name and location	(3) Position	(4) Characteristic	(5) Ht	(6) Rng	(7) Structure	(8) Remarks
28805	- Entrance Lighted Buoy 2	21 28 10 N 157 46 38 W *	Fl r 2.5s		4	Red.	17/04
28575	- Light	21 12 34 N 156 58 11 W *	Fl W 10s	213	21	On white tower. 138	Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. Operates during periods of darkness only. 16/04
29425	- Lighted Buoy 11	21 20 11 N 157 58 18 W *	Fl G 2.5s		5	Green.	
*	*	*	*	*	*	*	* 16/04
29535	- Lighted Buoy 6	*	Q R *	*	4 *	Red. *	* 16/04
29540	- Lighted Buoy 7	*	Q G *	*	4 *	Green. *	* 16/04
29543	- Lighted Buoy 8	*	Fl R 2.5s *	*	4 *	Red. *	* 16/04
No corrections this week							15/04
No corrections this week							14/04
28006	NOAA Data Lighted Buoy 51002	17 10 12 N 157 48 24 W *	Fl (4) Y 20s				Yellow boat-shaped weather buoy. 13/04
28008	NOAA Data Lighted Buoy 51001 *	23 25 55 N 162 12 28 W *	Fl (4) Y 20s				Yellow boat-shaped weather buoy. 13/04
No corrections this week							12/04
28380.5	- Range Front Daybeacon	20 53 43 N 156 28 43 W *		6		KRW on post.	Private aid. 11/04
28381	- Range Rear Daybeacon	20 53 43 N 156 28 45 W *		12		KRW on post.	Private aid. 11/04
29735	Kilauea Point Light	22 13 53 N 159 24 07 W	Fl W 10s	174	23	White concrete post. 10	Obscured from 295° to 065°. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. Operates during periods of darkness only. 10/04
	*				*		
28310	- CHANNEL SOUTH BREAKWATER LIGHT 6 *	20 02 12 N 155 50 00 W	Fl R 2.5s	20	4	TR on post. 12	10/04
29735	Kailua Point Light	22 13 53 N 159 24 07 W *	Fl W 10s	174	24	White concrete post. 10	Obscured from 295° to 065° Lighted throughout 24 hours. Emergency light of reduced Intensity when main light is extinguished. Operates during periods of darkness only. 09/04
No corrections this week							08/04
29-Apr-04							

Summary of corrections to Volume VI of the U.S. Coast Guard Light List for the 2003 edition.

(1) No.	(2) Name and location	(3) Position	(4) Characteristic	(5) Ht	(6) Rng	(7) Structure	(8) Remarks
28035	- Entrance Lighted Buoy 1	19 44 34 N 155 04 47 W *	Fl G 2.5s		5	Green.	07/04
28060	- RANGE FRONT LIGHT	19 43 57 N 155 03 12 W *	F G	75		KRW on post.	Visible 4° each side of rangeline. Lighted throughout 24 hours. 07/04
29060	Diamond Head Light	21 15 18 N 157 48 36 W	Oc (2) W 10s (R sector) 2s fl 1.5s ec. 5s fl 1.5s ec.	147	W 17 R 14	White concrete tower. 55	Obscured from 110° to 272° red from 099° to 110°. Between 105° to 110°, red sector may be obscured by vegetation. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. Operates during periods of darkness only. * 07/04
28035	- Entrance Lighted Buoy 1	19 44 34 N 155 04 47 W *	Fl G 2.5s		5	Green.	06/04
29405	- LIGHT 6		Fl R 4s	15	3 *	TR on pile.	06/04
28115	WAIKEA LIGHT						Remove from list * 05/04
28480	- Lighted Buoy 3 *	20 52 16 N 156 40 50 W *	Fl G 4s *			Green. *	Private aid. 05/04
28485	- Lighted Buoy 4 *		Fl R 4s *			Red. *	Private aid. 05/04
28490	- Lighted Buoy 5 *		Fl G 4s *			Green. *	Private aid. 05/04
28495	- Lighted Buoy 6 *		Fl R 4s *			Red. *	Private aid. 05/04
28500	- Lighted Buoy 7 *		Fl G 4s *			Green. *	Private aid. 05/04
28505	- Lighted Buoy 8 *		Fl R 4s *			Red. *	Private aid. 05/04
29850	Makahuena Point Light	21 52 06 N 159 26 36 W	Fl W 2.5s	80	8 *	NB on post. 20	Obscured from 110° to 237.5° 04/04
No corrections this week							03/04
No corrections this week							02/04
No corrections this week							01/04